- Al-powered noise isolation & voice clarity
- Environmental awareness with noise reduction
- Directional mic for clear communication
- Simple control buttons for mode & volume
- Bluetooth connectivity



SPECIFICATION BT / Bluetooth 5.3 Connector Battery up to 9 hours plus two **Battery Life** full charges in the case **Active Noise Reduction** -35 dB (Active + Passive) (ANR) 6*MEMS, Adaptive ambient sound, Ambient sound 3Filter,10 level volume (10 levels of volume adjustment, each level is 2dB.) **Immersion** Earbuds: IP67 / Charge case: IP55 earbud: 5.56q (PCS) / Weight charging case: 40.35g Certification CE, RoHs, NCC, BSMI, Telec



Vehicle Overhead

Active Noise Reduction Communication Headset with Built-in PTT

Tactical Overhead

Tactical Communication Hearing Protector with Situational Awareness





Personal **Protection**

Protective communication headset with boom microphone

CONTACT

XROUND





+886 02-8228-0106



xroundaudio.com



ben.ku@xroundaudio.com





- Active noise reduction headset
- Noise reduction rating: up to 28dB
- 360° ambient sound for auditory situational awareness
- Directional ECM boom microphone

www.xroundaudio.com

• Environmental awareness with noise reduction

- Directional mic for clear communication
- Simple control buttons for mode & volume
- Bluetooth connectivity
- · AA battery powered



AT-02

• Intelligent noise reduction headset for vehicle crews

- Al chip for clear communication & hearing protection
- Supports Bluetooth connectivity
- Compatible with DH-132 helmet



AT-03

SPECIFICATION

Connection	Wired / BT (Bluetooth 5.5)
Connector	AP107XL
Operating Voltage (external power)	5V
Battery	2x AAA 1.5 V (50Hours) Using battery power, whenIntercom system is powered off
Noise Reduction Rating (NRR)	Up to 28dB
Active Noise Reduction (ANR)	35 dB(Active + Passive)
Ambient Sound (Talk though)	2*MEMS, Ambient sound, 2 Filter, 10 level volume(10 levels of volume adjustment, each level is 2dB.)
Microphone Specification	Directional ECM boom microphone
PTT	PTT switch : ON (Intercom)-Off-Momentary (Radio operation) Dual PTT
Weight	750g
Environmental Tests	MIL- STD-810G
Electromagnetic Compatibility	MIL-STD-461

- Tactical headset for radio
- Provides hearing protection & clear communication

- 360° ambient sound for auditory situational awareness
- Directional ECM boom microphone
- Noise Reduction Rating : Up to 28dB



AT-04

SPECIFICATION

	SPECIFICATION
Connector	Wired / BT (Bluetooth 5.5)
Battery	2x AAA 1.5 V
Battery Life	100 Hours
Noise Reduction Rating (NRR)	Up to 28dB
Active Noise Reduction (ANR)	-35 dB (Active + Passive)
Ambient Sound	2*MEMS, Ambient sound , 2 Filter, 10 level volume (10 levels of volume adjustment, each level is 2dB.)
Boom Microphone Specification	IP67 MIC ECM Mircophone(2.0V), Impedance : 2KΩ± @1kHz, Frequency : 100-10KHz
Weight	392g
Environmental Tests	MIIL- STD-810G
Electromagnetic Compatibility	MIL-STD-461

	SPECIFICATION
Connection	Wired / BT (Bluetooth 5.5)
Connector	AUX
Battery	2x AA 1.5 V
Battery Life	150Hours
Noise Reduction Rating (NRR)	Up to 28dB
Microphone Specification	Directional ECM boom microphone
Ambient Sound	2*MEMS, Ambient sound, 2 Filter, 10 level volume(10 levels of volume adjustment, each level is 2dB.)
Speaker Specification	30mm
Weight	310g
Environmental Tests	ANSI S3.19-1974/EN352, NZS 1270
Certification	CE, RoHS